



Hosiden Besson Ltd  
St. Joseph's Close  
Brighton & Hove  
East Sussex BN3 7EZ  
England  
Tel: +44 1273 861166  
Fax: +44 1273 777501  
Email: info@hbl.co.uk  
www.hbl.co.uk

# product sheet

## Bedroom Sounders 24V Low Frequency

- Flush mount Sounder is CPD & LPCB approved to EN54-3
- Low Current Consumption
- Dual sound options selected via a jumper switch
- Both Flush and Surface mounted
- Robust terminal connectors to accommodate up to 2.5mm conductors

The Flush Mount Bedroom Sounder is EN54-3: 2001 and CPD approved as an indoor low current 2 tone sounder for the fire alarm marker. Designed to be aesthetically un-intrusive for use in hotel bedrooms, restaurants and residential environments, being able to fit into a 25mm deep 1 gang flush or surface mounted patress box. The FM Bedroom Sounder is available in White or Red flame retardant ABS. Also available is the Bedroom Sounder LF designed to meet the requirements of BS5839 part 1.

These Bedroom Sounders complement a comprehensive range of sounders which have been designed and built with quality, reliability and the requirements of the end user foremost in mind, allowing a wide spectrum of Fire and Security applications to be serviced.



# Bedroom sounders

24V Low Frequency

	<b>FM (Flush Mount) Bedroom Sounder</b>	<b>Bedroom Sounder</b>
<b>Dimensions</b>	85mm x 85mm x 30mm deep	86mm x 86mm x 55mm deep
<b>Typical Current Consumption</b>	7mA	14mA
<b>Max Volume</b>	90dBA @ 1m (typical)	96dBA @ 1m (typical) Min 60dBA @ 1m
<b>Frequency: Fast Sweep Continuous</b>	800-970Hz (@ 9Hz) 850Hz	800-950Hz (@ 9Hz) 850Hz
<b>Input</b>	24 Volts DC	24 Volts DC
<b>Installation</b>	Surface or Flush mounted using 25mm deep patress box.	Surface mounted. Rear or side cable entry.
<b>Colours</b>	Red or White, Flame retardant ABS.	White, High impact ABS.
<b>Connections</b>	2 in, 2 out, each 2.5mm max	2 in, 2 out, each 2.5mm max